2021

COMMANDER DPS 1000R

HIGHLIGHTS

DARING	 Sturdy engine and transmission Enhanced comfort and meaningful functionalities Can-Am design
PRECISE	 Easy handling and capabilities Suspension designed for performance Ultra-resistant chassis
CAPABLE	Work or ride with confidence Meaningful and versatile functionality Easy handling and capabilities
PLATFORM FEATURES	90.6 in, wheelbase 12.5 in, ground clearance Up to 13 in, of suspension travel 2,000 lb towing capacity Dynamic Power Steering (DPS™) Visco-Lok¹ QE front differential SPORT/ECO™ modes D.E.S.S. key with Start/Stop button 4.5 in, digital display Premium half door Mudguard Rear differential with Turf mode

ENGINE	1000R
Туре	100 hp, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Selectable Turf Mode/2WD/4WD with Visco-Lok† QE auto-locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Double A-arm with sway bar/12.5 in. (31.8 cm) travel
Front Shocks	Twin-tube gas-charged shocks
Rear Suspension	TTA with sway bar/13 in. (33 cm) travel
Rear Shocks	Twin-tube gas-charged shocks

TIRES & WHEELS

Front Tires	XPS Trail Force 27 x 9 x 14 in. (68.6 x 22.9 x 35.6 cm)
Rear Tires	XPS Trail Force 27 x 11 x 14 in. (68.6 x 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) steel

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers



Tundra Green / 1000R

DIMENSIONS & CAPACITIES

DIMENSIONS & CAPACITIES		
Estimated Dry Weight	1,600 lb (725.5 kg)	
Chassis/Cage	Profiled cage, ROPS approved	
LxWxH	128.2 x 62 x 71.5 in (325.6 x 157.5 x 181.6 cm)	
Wheelbase	90.6 in. (230.1 cm)	
Ground Clearance	12.5 in (31.8 cm)	
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in, (75.1 x 114.7 x 27 cm)	
Cargo Box Capacity	600 lb (272.2 kg)	
Towing Capacity	2,000 lb (907.2 kg)	
Payload Capacity	1,030 lb (467.2 kg)	
Storage Capacity	Total: 7.3 gal (27.6 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and our bolders: 0.8 gal (3.1 L)	

Center console and cup holders: 0.8 gal (3.1 L) Side cargo box storage (passenger side): 1.6 gal (5.9 L) Dual side panel storage: 0.8 gal (3.0 L)

2 years BRP limited warranty

Fuel Capacity 10 gal (38 L)

FEATURES

WARRANTY	
Hitch Type	2 in, hitch receiver
	Mudguards
	Full skid plate
Protection	Premium half doors
Steering Wheel	Adjustable tilt steering
Winch	N/A
Lighting	Two 55 W reflector headlights (low/high) and LED taillights
Magneto	650 W
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Instrumentation	Lighter-type DC outlet in console (10 A)
Gauge	4.5 in. (11.4 cm) wide digital display: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature

© 2020 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®. TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc., † Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinuou or change specifications, prices, designs, features, models or equipment without curring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) operator's guide and watch the safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SSVs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 19 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in sturnt driving and avoid excessives speed. Ride responsibly.

Factory Warranty

